

Epilox[®] M 985

Description Epilox[®] M 985 is an aliphatic diglycidyl ether which is used as reactive diluent with flexibilizing properties for epoxy resins

Data	Viscosity at 25 °C (DIN 53 015)	mPa·s	40 - 90
	Epoxy Equivalent Weight (DIN 16 945)	g	425 - 500
	Density at 20 °C (DIN 53 217 T.4)	g/cm ³	ca 1.03
	Colour Number (Gardner) (DIN ISO 4630)	-	< 2

Uses Reactive diluent with flexibilizing properties for epoxy resins.
Epilox[®] M 985 is easily miscible with epoxy resins and can therefore be used to reduce the viscosity of standard epoxy resins, e.g. Epilox[®] A 19-00 or Epilox[®] A 19-02.

Packing/Storage/Transportation Epilox[®] M 985 is supplied in containers or drums.
The product should be stored in closed containers at temperatures of about 20 °C. Under these storage conditions, Epilox[®] M 985 shows no change in quality even after prolonged storage time exceeding 12 months.

Safety Requirements Please refer to the valid Material Safety Data Sheet as well as to the legal and recommended industrial hygiene regulations.

The information given in these data is based on the testing methods established by Leuna-Harze GmbH and on the knowledge of the characteristics of Epilox[®]- products and is given in good faith. No liability is accepted by Leuna-Harze GmbH for any system or application in which Epilox[®]- products are utilized.