

Epilox[®] P 14-12G

Description Epilox[®] P 14-12G is a clear, colourless liquid with a biobased carbon content of about 23 %.

Application Reactive diluent for epoxy resins. Epilox[®] P 14-12G is easily miscible with epoxy resins and can therefore be used to reduce the viscosity of standard epoxy resins, e.g. Epilox[®] A 19-00 or Epilox[®] A 19-02.

Data

Viscosity at 25 °C (DIN 53 015)	mPa·s	20 – 30
Epoxy Equivalent Weight (DIN 16 945)	g / eq	211 – 235
Colour Number (Gardner) (DIN EN ISO 4630)	–	< 2

**Packing /
Storage / Transport**

Epilox[®] P 14-12G is supplied in drums, containers or road tankers. The product should be stored in closed containers at temperatures between 10 °C and 30 °C to protect it from moisture. Under these storage conditions, Epilox[®] P 14-12G shows no change in quality even after prolonged storage time exceeding 12 months.

Safety Requirements

Please refer to the valid Material Safety Data Sheet as well as to the legal and recommended industrial hygiene regulations.

Data Sheet



The information given in these data is based on the testing methods established by Leuna-Harze GmbH and on the knowledge of the characteristics of Epilox[®] - products and is given in good faith. No liability is accepted by Leuna-Harze GmbH for any system or application in which Epilox[®]- products are utilized.